



<b>BRICK NAME(S)</b>	Dual Faced Pressed Red.
<b>BRICK TYPE</b>	Through colour clay pressed brick.
<b>SPECIFICATION</b>	Manufactured to AS/NZS 4455 and BS EN 771-1:2011.
<b>SIZE*</b>	Nominal 73 x 215 x 102.5mm.
<b>DIMENSIONAL TOLERANCE</b>	DPB3 size classification, +/- 2mm 1 sigma standard deviation from the nominal size (n=20) is to be expected.
<b>COMPRESSIVE STRENGTH</b>	Mean – 44.8 N/MM <sup>2</sup>
<b>WATER ABSORPTION</b>	Mean - 22%
<b>SOLUBLE SALT CLASSIFICATION</b>	S2
<b>BULK DENSITY</b>	1500 kg/m
<b>PACKAGING</b>	Shrink wrapped on wooden pallets in packs of <ul style="list-style-type: none"><li>• 540 bricks to pallet.</li></ul>
<b>PACK SIZE</b>	L x W x H 1100 x 1100 x 1100mm Approx.
<b>PACK WEIGHT</b>	1.5 to 1.6 Tonnes Approx.
<b>USAGE</b>	Always mix from several packs.
<b>DURABILITY</b>	General Purpose Building Brick (AS/NZS 4455) F2 BS EN771-1:2011
<b>PERFORMANCE</b>	<ul style="list-style-type: none"><li>• The recommendations of good practice made in the relevant Think Brick guides regarding design and workmanship must be fully observed. Liability cannot be accepted for the performance of the product if used outside our recommendations.</li><li>• Guidance on the use of these bricks in specific situations is readily available from us.</li></ul>

\*Individual bricks may vary dimensionally; this is a natural characteristic of fired clay bricks and is catered for in the relevant Australian, New Zealand and European Standards.  
info@elephantbrickco.com.au